# ZEN MINI 3000, 940, FLOOD W/ GLASS, WHITE

- Pure and minimalistic/clean design
- Design puro e essenziale/pulito
- Quattro diverse angolazioni del fascio per la distribuzione della luce
- Alimentatore elettronico integrato
- Sorgente luminosa a LED ad alta efficienza con tecnologia “Chip on board”








## TECHNICAL SPECIFICATION

| | |
|---|---|
| Product Code | 325-508-10 |
| Colour | White |
| Control | On/off |
| CRI light colour | 940 |
| Delivered lumen output lm | 2800 |
| Driver | Built in |
| EEI | E |
| Light distribution | Flood |
| Lightsource | LED COB |
| Mains input voltage | 220-240V |
| Measurements A | 194 |
| Measurements B | 135 |
| Measurements C | 86 |
| Mounting | Track |
| Position | 360Â°/90Â° |
| Lifetime | L80 B10, 50.000h |
| Protection | IP 20, class I |
| Start Time | Instant |
| System power W | 24,5 |
| Unit | mm |
| Weight | 0,65 |




A= 194mm, B= 135mm, C= 86mm

| Spot | | Medium | | Flood | | Wide Flood | |
|---|---|---|---|---|---|---|---|
| | 18° | | 31° | | 42° | | 60° |
| m | ø | m | ø | m | ø | m | ø |
| 1.0 | 0.31 | 1.0 | 0.52 | 1.0 | 0.76 | 1.0 | 1.16 |
| 2.0 | 0.62 | 2.0 | 1.05 | 2.0 | 1.52 | 2.0 | 2.32 |
| 3.0 | 0.93 | 3.0 | 1.57 | 3.0 | 2.28 | 3.0 | 3.48 |

**ITAB Lighting**
**Europe, Asia, Middle East**
Phone: +46 910 733 790
info@nordiclight.se

**ITAB Lighting**
**North America**
Phone: +1 614 421 8419
na@nordiclight.se

*Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours*