

Zen Evo Mini, Black, 3000, 930, Medium, segmented, Track


ITAB

- ✓ □ Design estremamente essenziale/pulito
- ✓ □ Sorgente luminosa LED con tecnologia "Chip on board" ad alta efficienza e riflettore segmentato per la massima efficacia
- ✓ □ Alimentatore elettronico ad alta efficienza integrato nell'adattatore per binario
- ✓ □ Sorgente luminosa a LED ad alta efficienza con tecnologia "Chip on board"
- ✓ □ Disponibile in bianco, nero e grigio.



Technical specification

Product Code	367-02071520013
Colour	Black
Control	On/off
CRI light colour	930 (BBBL)
Delivered lumen output lm	2950
Driver	Built in
EEL	E
Light distribution	Medium
Lightsource	LED COB
Mains input voltage	220-240V
Measurements A	86
Measurements B	106
Measurements C	164
Measurements D	206
Measurements E	134
Mounting	Track
Position	360°/90°
Lifetime	L80 B10 50.000h
Protection	IP 20, class II
Start Time	Instant
System power W	18,8
Unit	mm
Weight	0,49



A= 86 mm, B= 106 mm, C= 164 mm, D= 206 mm

Spot	Medium	Flood	Wide Flood
19°	29°	49°	70°
m	m	m	m
1.0	0.31	0.52	0.76
2.0	0.62	1.05	1.52
3.0	0.93	1.57	2.28
			3.48