# Zen Evo, Black, 2500, 930, Spot, segmented, Track

- Design estremamente essenziale/pulito
- Elevata emissione di lumen perfetta per punti vendita dei settori dei generi alimentari e fai da te
- Sorgente luminosa LED con tecnologia “Chip on board” ad alta efficienza e riflettore segmentato per la massima efficacia
- Alimentatore elettronico ad alta efficienza integrato nell'adattatore per binario
- Disponibile in bianco, nero e grigio.

## Technical specification

| | |
|---|---|
| Product Code | 369-02061510013 |
| Colour | Black |
| Control | On/off |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 2400 |
| Driver | Built in |
| EEI | E |
| Light distribution | Spot |
| Lightsource | LED COB |
| Mains input voltage | 220-240V |
| Measurements A | 206 |
| Measurements B | 194 |
| Measurements C | 222 |
| Measurements D | 128 |
| Mounting | Track |
| Position | 360°/90° |
| Lifetime | L80 B10, 50.000h |
| Protection | IP 20, class II |
| Start Time | Instant |
| System power W | 15,0 |
| Unit | mm |
| Weight | 0,7 |




A= 206 mm, B=194 mm, C=222 mm,
D= 128 mm, E=104 mm

| Spot | | Medium | | Flood | | Wide Flood | |
|---|---|---|---|---|---|---|---|
| | 16° | | 29° | | 40° | | 60° |
| m | ø | m | ø | m | ø | m | ø |
| 1.0 | 0.31 | 1.0 | 0.52 | 1.0 | 0.76 | 1.0 | 1.16 |
| 2.0 | 0.62 | 2.0 | 1.05 | 2.0 | 1.52 | 2.0 | 2.32 |
| 3.0 | 0.93 | 3.0 | 1.57 | 3.0 | 2.28 | 3.0 | 3.48 |

**ITAB Lighting**
**Europe, Asia, Middle East**
Phone: +46 910 733 790
info@nordiclight.se

**ITAB Lighting**
**North America**
Phone: +1 614 421 8419
na@nordiclight.se

*Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours*