


AMBER MINI 2500, 930 (BBBL), MEDIUM, GREY

ITAB

- ✓ Techo discreto y de aspecto limpio
- ✓ Disponible en varios tamaños y paquetes de lúmenes
- ✓ Instalación sin herramientas
- ✓ Disponible en blanco, negro y gris
- ✓ Retráctil y giratorio

TECHNICAL SPECIFICATION

| | |
|------------------------------|-----------------------|
| Product Code | 296-546-30 |
| Colour | Grey |
| Control | On/off |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 2350 |
| Driver | Stand alone, included |
| EEL | E |
| Light distribution | Medium |
| Lightsource | LED COB |
| Mains input voltage | 220-240 V |
| Measurements A | 131 |
| Measurements B | 101 |
| Measurements C | 114 |
| Mounting | Recessed |
| Position | 360°/60° |
| Lifetime | L80 B10, 50.000h |
| Protection | IP 20, class III |
| Sawing instructions diameter | 124 |
| Start Time | Instant |
| System power W | 18,8 |
| Unit | mm |
| Weight | 0,55 |



A= 131mm
B= 101mm
C= 114mm

| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 16° | 28° | 40° | 65° |
| m | ø | m | ø |
| 1.0 | 0.28 | 1.0 | 0.73 |
| 2.0 | 0.56 | 2.0 | 1.46 |
| 3.0 | 0.83 | 3.0 | 2.18 |
| 1.0 | 0.50 | 1.0 | 1.28 |
| 2.0 | 1.00 | 2.0 | 2.56 |
| 3.0 | 1.51 | 3.0 | 3.84 |



124mm