

FLEXO (H) 3000, 930 (BBBL), SPOT, WHITE

ITAB


- ✓ Techo moderno, minimalista y de aspecto limpio
- ✓ Disponible en varios paquetes de lúmenes
- ✓ Instalación sin herramientas
- ✓ Disponible en blanco, negro y gris
- ✓ Inclínable y giratorio

TECHNICAL SPECIFICATION

| | |
|------------------------------|-----------------------|
| Product Code | 306-730-10 |
| Colour | White |
| Control | On/off |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 2841 |
| Driver | Stand alone, included |
| EEL | E |
| Light distribution | Spot |
| Lightsource | LED COB |
| Mains input voltage | 220-240V |
| Measurements A | 211 |
| Measurements B | 65 |
| Measurements C | 70 |
| Mounting | Recessed |
| Position | 360°/60° |
| Lifetime | L80 B10 50.000h |
| Protection | IP 20, class III |
| Sawing instructions diameter | Ø200 |
| Start Time | Instant |
| System power W | 21,6 |
| Unit | mm |
| Weight | 1,1 |



A= 176mm, B= 65mm, C= 70mm



| Spot | | Medium | | Flood | | Wide Flood | |
|------|------|--------|------|-------|------|------------|------|
| 14° | | 27° | | 38° | | 56° | |
| m | ø | m | ø | m | ø | m | ø |
| 1.0 | 0.25 | 1.0 | 0.48 | 1.0 | 0.69 | 1.0 | 1.07 |
| 2.0 | 0.49 | 2.0 | 0.95 | 2.0 | 1.39 | 2.0 | 2.14 |
| 3.0 | 0.74 | 3.0 | 1.43 | 3.0 | 2.08 | 3.0 | 3.22 |



165mm