

# Titan 4000, 930 (BBBL), Medium w/ glass, Grey

ITAB

- ✓ Soffitto discreto e pulito
- ✓ Disponibile in varie dimensioni e pacchetti di lumen
- ✓ Installazione senza attrezzi
- ✓ Disponibile in bianco, nero e grigio



## Technical specification

|                              |                                                      |
|------------------------------|------------------------------------------------------|
| Product Code                 | 271-511-30                                           |
| Colour                       | Grey                                                 |
| Control                      | On/off                                               |
| CRI light colour             | 930 (BBBL)                                           |
| Delivered lumen output lm    | 3700                                                 |
| Driver                       | Stand alone, included                                |
| EEL                          | E                                                    |
| Light distribution           | Medium                                               |
| Lightsource                  | LED COB                                              |
| Mains input voltage          | 220-240 V                                            |
| Measurements A               | 144                                                  |
| Measurements B               | 90                                                   |
| Mounting                     | Recessed                                             |
| Position                     | Fixed                                                |
| Lifetime                     | L80 B10, 50.000h                                     |
| Protection                   | IP20/IP44 with front glass. IP20 without front glass |
| Sawing instructions diameter | 128                                                  |
| Start Time                   | Instant                                              |
| System power W               | 29,4                                                 |
| Unit                         | mm                                                   |
| Weight                       | 0,55                                                 |



| Spot | 14°  | Medium | 26°  | Flood | 37°  | Wide Flood | 55°  |
|------|------|--------|------|-------|------|------------|------|
| m    | ø    | m      | ø    | m     | ø    | m          | ø    |
| 1.0  | 0.24 | 1.0    | 0.47 | 1.0   | 0.68 | 1.0        | 1.05 |
| 2.0  | 0.48 | 2.0    | 0.94 | 2.0   | 1.35 | 2.0        | 2.10 |
| 3.0  | 0.72 | 3.0    | 1.41 | 3.0   | 2.03 | 3.0        | 3.15 |



128mm