# ZEN MINI 3000, 930 (BBBL), SPOT W/ GLASS, GREY

ITAB

- Design épuré et minimaliste
- Source LED « chip on board » haute performance et réflecteur segmenté offrant une efficacité maximale
- Système de commande électronique haute performance intégré à l'adaptateur
- Quatre faisceaux différents pour la répartition de la lumière
- Disponible en blanc, noir et gris.








## TECHNICAL SPECIFICATION

| | |
|---|---|
| Product Code | 325-500-30 |
| Colour | Grey |
| Control | On/off |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 2801 |
| Driver | Built in |
| EEI | E |
| Light distribution | Spot |
| Lightsource | LED COB |
| Mains input voltage | 220-240V |
| Measurements A | 194 |
| Measurements B | 135 |
| Measurements C | 86 |
| Mounting | Track |
| Position | 360Â°/90Â° |
| Lifetime | L80 B10, 50.000h |
| Protection | IP 20, class I |
| Start Time | Instant |
| System power W | 21 |
| Unit | mm |
| Weight | 01.05 |




A= 194mm, B= 135mm, C= 86mm

| Spot | | Medium | | Flood | | Wide Flood | |
|---|---|---|---|---|---|---|---|
| | 18° | | 31° | | 42° | | 60° |
| m | ø | m | ø | m | ø | m | ø |
| 1.0 | 0.31 | 1.0 | 0.52 | 1.0 | 0.76 | 1.0 | 1.16 |
| 2.0 | 0.62 | 2.0 | 1.05 | 2.0 | 1.52 | 2.0 | 2.32 |
| 3.0 | 0.93 | 3.0 | 1.57 | 3.0 | 2.28 | 3.0 | 3.48 |

**ITAB Lighting**
**Europe, Asia, Middle East**
Phone: +46 910 733 790
info@nordiclight.se

**ITAB Lighting**
**North America**
Phone: +1 614 421 8419
na@nordiclight.se

*Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours*