Zen Evo, Black, 2500, 930, Spot, segmented, Track

- Design très dépouillé/minimaliste
- Rendement lumineux élevé, idéal pour les magasins dédiés à l'alimentation et à l'amélioration de l'habitat
- Source LED « chip on board » haute performance et réflecteur segmenté offrant une efficacité maximale
- Système de commande électronique haute performance intégré à l'adaptateur
- Disponible en blanc, noir et gris.

Technical specification

Product Code	369-02061510013
Colour	Black
Control	On/off
CRI light colour	930 (BBBL)
Delivered lumen output lm	2400
Driver	Built in
EEI	E
Light distribution	Spot
Lightsource	LED COB
Mains input voltage	220-240V
Measurements A	206
Measurements B	194
Measurements C	222
Measurements D	128
Mounting	Track
Position	360°/90°
Lifetime	L80 B10, 50.000h
Protection	IP 20, class II
Start Time	Instant
System power W	15,0
Unit	mm
Weight	0,7



A= 206 mm, B=194 mm, C=222 mm,
D= 128 mm, E=104 mm

Spot		Medium		Flood		Wide Flood	
	16°		29°		40°		60°
m	ø	m	ø	m	ø	m	ø
1.0	0.31	1.0	0.52	1.0	0.76	1.0	1.16
2.0	0.62	2.0	1.05	2.0	1.52	2.0	2.32
3.0	0.93	3.0	1.57	3.0	2.28	3.0	3.48

ITAB Lighting
Europe, Asia, Middle East
Phone: +46 910 733 790
info@nordiclight.se

ITAB Lighting
North America
Phone: +1 614 421 8419
na@nordiclight.se

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours