

# Zen Evo, Black, 4000, 930, Spot, segmented, Track

ITAB

- ✓ □ Design très dépouillé/minimaliste
- ✓ □ Rendement lumineux élevé, idéal pour les magasins dédiés à l'alimentation et à l'amélioration de l'habitat
- ✓ □ Source LED « chip on board » haute performance et réflecteur segmenté offrant une efficacité maximale
- ✓ □ Système de commande électronique haute performance intégré à l'adaptateur
- ✓ □ Disponible en blanc, noir et gris.



## Technical specification

|                           |                  |
|---------------------------|------------------|
| Product Code              | 369-02091510013  |
| Colour                    | Black            |
| Control                   | On/off           |
| CRI light colour          | 930 (BBBL)       |
| Delivered lumen output lm | 3950             |
| Driver                    | Built in         |
| EEL                       | E                |
| Light distribution        | Spot             |
| Lightsource               | LED COB          |
| Mains input voltage       | 220-240V         |
| Measurements A            | 162              |
| Measurements B            | 194              |
| Measurements C            | 222              |
| Measurements D            | 128              |
| Mounting                  | Track            |
| Position                  | 360°/90°         |
| Lifetime                  | L80 B10, 50.000h |
| Protection                | IP 20, class II  |
| Start Time                | Instant          |
| System power W            | 26,6             |
| Unit                      | mm               |
| Weight                    | 0,7              |



A= 206 mm, B=194 mm, C=222 mm,  
D= 128 mm, E=104 mm

| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 16°  | 29°    | 40°   | 60°        |
| m    | m      | m     | m          |
| 1.0  | 0.31   | 0.52  | 0.76       |
| 2.0  | 0.62   | 1.05  | 1.52       |
| 3.0  | 0.93   | 1.57  | 2.28       |