


FLEX II 3000, 930 (BBBL), SPOT W/ GLASS, WHITE

ITAB

- ✓ Moderni, minimalistinen ja siisti
- ✓ Saatavilla eri lumeneissa
- ✓ Asennus ilman työkaluja
- ✓ Saatavilla valkoisena, mustana ja harmaana
- ✓ Upotettava ja kääntyvä

TECHNICAL SPECIFICATION

Product Code	306-21071110062
Colour	White
Control	On/off
CRI light colour	930 (BBBL)
Delivered lumen output lm	2 x 2841
Driver	Stand alone, included
EEI	E
Light distribution	Spot
Lightsource	LED COB
Mains input voltage	220-240 V
Measurements A	202
Measurements B	179
Measurements C	363
Measurements D	70
Mounting	Recessed
Position	360°/60°
Lifetime	L80 B10, 50.000h
Protection	IP 20, class III
Sawing instructions x	177
Sawing instructions y	352
Start Time	Instant
System power W	2 x 21,6
Unit	mm
Weight	1,9



Spot	Medium	Flood	Wide Flood
14°	27°	38°	56°
m	m	m	m
1.0	1.0	1.0	1.0
2.0	2.0	2.0	2.0
3.0	3.0	3.0	3.0
0.25	0.48	0.69	1.07
0.49	0.95	1.39	2.14
0.74	1.43	2.08	3.22



177 x 352mm