

# Titan Micro 1200, 930 (BBBL), Wide Flood w/ glass, White


ITAB

- ✓ Huomaamaton ja siisti
- ✓ Saatavilla eri kokovaihtoehtoissa ja valovirtapaketeissa
- ✓ Asennus ilman työkaluja
- ✓ Saatavilla valkoisena, mustana ja harmaana



## Technical specification

|                              |                       |
|------------------------------|-----------------------|
| Product Code                 | 328-503-10            |
| Colour                       | White                 |
| Control                      | On/off                |
| CRI light colour             | 930 (BBBL)            |
| Delivered lumen output lm    | 1150                  |
| Driver                       | Stand alone, included |
| EEL                          | E                     |
| Light distribution           | Wide flood            |
| Lightsource                  | LED COB               |
| Mains input voltage          | 220-240 V             |
| Measurements A               | 71                    |
| Measurements B               | 42                    |
| Mounting                     | Recessed              |
| Position                     | Fixed                 |
| Lifetime                     | L80 B10, 50.000h      |
| Protection                   | IP 20, class III      |
| Sawing instructions diameter | 64                    |
| Start Time                   | Instant               |
| System power W               | 11                    |
| Unit                         | mm                    |
| Weight                       | 0,2                   |



A= 71mm, B= 42mm

| Spot | 15°  | Medium | 27°  | Flood | 36°  | Wide Flood | 56°  |
|------|------|--------|------|-------|------|------------|------|
| m    | ø    | m      | ø    | m     | ø    | m          | ø    |
| 1.0  | 0.26 | 1.0    | 0.47 | 1.0   | 0.65 | 1.0        | 1.06 |
| 2.0  | 0.53 | 2.0    | 0.95 | 2.0   | 1.30 | 2.0        | 2.12 |
| 3.0  | 0.79 | 3.0    | 1.42 | 3.0   | 1.95 | 3.0        | 3.18 |



64mm