

# ORION I 2000, 930 (BBBL), FRAME, SPOT W/ GLASS, WHITE

ITAB

- ✓ Huomaamaton ja siistin näköinen katto
- ✓ Käännä valoa 30° mihin tahansa suuntaan
- ✓ Saatavilla valkoisena, mustana ja harmaana

## TECHNICAL SPECIFICATION

|                           |                       |
|---------------------------|-----------------------|
| Product Code              | 300-11051110062       |
| Colour                    | White                 |
| Control                   | On/off                |
| CRI light colour          | 930 (BBBL)            |
| Delivered lumen output lm | 1689                  |
| Driver                    | Stand alone, included |
| EEL                       | E                     |
| Light distribution        | Spot                  |
| Lightsources              | LED COB               |
| Mains input voltage       | 220-240 V             |
| Measurements A            | 165                   |
| Measurements B            | 158                   |
| Measurements C            | 103                   |
| Mounting                  | Recessed              |
| Position                  | 360°/30°              |
| Lifetime                  | L80 B10, 50.000h      |
| Protection                | IP 20, class III      |
| Sawing instructions x     | 157                   |
| Sawing instructions y     | 150                   |
| Start Time                | Instant               |
| System power W            | 12,5                  |
| Unit                      | mm                    |
| Weight                    | 0,9                   |



| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 16°  | 28°    | 40°   | 65°        |
| m    | m      | m     | m          |
| 0    | 0      | 0     | 0          |
| 1.0  | 0.28   | 0.73  | 1.28       |
| 2.0  | 0.56   | 1.46  | 2.56       |
| 3.0  | 0.83   | 2.18  | 3.84       |



272 x 150mm