


TITAN 4000, 930 (BBBL), SPOT, WHITE

ITAB

- ✓ Diskret och rent tak
- ✓ Finns i olika storlekar och lumenpaket
- ✓ Verktygsfri installation
- ✓ Finns i vitt, svart och grått

TECHNICAL SPECIFICATION

| | |
|------------------------------|--|
| Product Code | 271-510-10 |
| Colour | White |
| Control | On/off |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 3780 |
| Driver | Stand alone, included |
| EEL | E |
| Light distribution | Spot |
| Lightsource | LED COB |
| Mains input voltage | 220-240 V |
| Measurements A | 144 |
| Measurements B | 90 |
| Mounting | Recessed |
| Position | Fixed |
| Lifetime | L80 B10, 50.000h |
| Protection | IP20/IP44 with front glass. IP20 without front glass |
| Sawing instructions diameter | 128 |
| Start Time | Instant |
| System power W | 32,8 |
| Unit | mm |
| Weight | 0,55 |



A= 144mm, B= 90mm

| Spot | Medium | | Flood | | Wide Flood | | |
|------|--------|-----|-------|-----|------------|-----|------|
| | 14° | 26° | 37° | 55° | | | |
| m | ø | m | ø | m | ø | m | ø |
| 1.0 | 0.24 | 1.0 | 0.47 | 1.0 | 0.68 | 1.0 | 1.05 |
| 2.0 | 0.48 | 2.0 | 0.94 | 2.0 | 1.35 | 2.0 | 2.10 |
| 3.0 | 0.72 | 3.0 | 1.41 | 3.0 | 2.03 | 3.0 | 3.15 |



128mm