



ZIMLED 1200, 930 (BBBL), SPOT W/ GLASS, BLACK

ITAB

- ✓ Diskret og ren himling.
- ✓ Tilgjengelig i fire forskjellige fargetemperaturer
- ✓ Verktøyfri installasjon
- ✓ Tilgjengelig i hvit, svart og grå
- ✓ Enkel justering

TECHNICAL SPECIFICATION

Product Code	303-500-20
Colour	Black
Control	On/off
CRI light colour	930 (BBBL)
Delivered lumen output lm	1150
Driver	Stand alone, included
EEL	E
Light distribution	Spot
Lightsource	LED COB
Mains input voltage	220-240 V
Measurements A	118
Measurements B	56
Measurements C	61
Mounting	Recessed
Position	355°/80°
Lifetime	L80 B10, 50.000h
Protection	IP 20, class III
Sawing instructions diameter	108
Start Time	Instant
System power W	11
Unit	mm
Weight	0,2



A= 118mm, B= 56mm, C= 61mm

Spot	Medium	Flood	Wide Flood
15°	27°	36°	56°
m	ø	m	ø
1.0	0.26	1.0	0.47
2.0	0.53	2.0	0.95
3.0	0.79	3.0	1.42
1.0	0.47	1.0	0.65
2.0	0.95	2.0	1.30
3.0	1.42	3.0	1.95
1.0	0.65	1.0	1.06
2.0	1.30	2.0	2.12
3.0	1.95	3.0	3.18



108mm