# OPUS II, 1500, 930, NA, Retrofit kit, Medium, White, 120-277V

- ✓ Product is title 24 compatible
- ✓ Discrete and clean-looking ceiling
- ✓ Swivel the light up to 30˚ in any direction
- ✓ Available in white, black and grey

## Technical specification

| | |
|---|---|
| Product Code | 324-402-102-10 |
| Colour | White |
| Control | On/off |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 2700 |
| Driver | Stand alone, included |
| EEI | E |
| Light distribution | Medium, Medium |
| Lightsource | LED COB |
| Mains input voltage | 120V |
| Measurements A | 11 |
| Measurements B | 6,3 |
| Measurements C | 4,13 |
| Mounting | Recessed |
| Position | Vertical/Gyro |
| Lifetime | L80 B10 50.000h |
| Protection | IP 20, class III |
| Sawing instructions unit | inch |
| Sawing instructions x | 5,9 |
| Sawing instructions y | 10,7 |
| Start Time | Instant |
| System power W | 21,49 |
| Unit | inch |
| Weight | 3,3 lbs |

A= 11in
B= 17,6in
C= 5,5in
D= 11,1in
E= 6,2in

| Spot | | Medium | | Flood | | Wide Flood | |
|---|---|---|---|---|---|---|---|
| 16° | | 28° | | 40° | | 65° | |
| m | ø | m | ø | m | ø | m | ø |
| 1.0 | 0.28 | 1.0 | 0.50 | 1.0 | 0.73 | 1.0 | 1.28 |
| 2.0 | 0.56 | 2.0 | 1.00 | 2.0 | 1.46 | 2.0 | 2.56 |
| 3.0 | 0.83 | 3.0 | 1.51 | 3.0 | 2.18 | 3.0 | 3.84 |

5,9 x 10,7in

*Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours*