

FLEX III, 3000, 930, NA, Retrofit kit, Spot, Wide Flood, Medium, White, 120-277V


ITAB

- ✓ Product is title 24 compatible
- ✓ Modern, minimalistic and clean-looking ceiling
- ✓ Available in various lumen packages
- ✓ Available in white, black and grey
- ✓ Tiltable and rotating



Technical specification

| | |
|---------------------------|--------------------------|
| Product Code | 306-403-207-10 |
| Colour | White |
| Control | On/off |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 2700 |
| Driver | Stand alone, included |
| EEI | E |
| Light distribution | Spot, Wide Flood, Medium |
| Lightsource | LED COB |
| Mains input voltage | 120V |
| Measurements A | 20,6 |
| Measurements B | 2,75 |
| Measurements C | 8 |
| Measurements D | 7 |
| Mounting | Recessed |
| Position | 360°/60° |
| Lifetime | L80 B10 50.000h |
| Protection | IP 20, class III |
| Sawing instructions unit | inch |
| Sawing instructions x | 20,1 |
| Sawing instructions y | 6,7 |
| Start Time | Instant |
| System power W | 21,49 |
| Unit | inch |
| Weight | 6,17 lbs |



| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 14° | 27° | 38° | 56° |
| m | m | m | m |
| 1.0 | 1.0 | 1.0 | 1.0 |
| 2.0 | 2.0 | 2.0 | 2.0 |
| 3.0 | 3.0 | 3.0 | 3.0 |
| 0.25 | 0.48 | 0.69 | 1.07 |
| 0.49 | 0.95 | 1.39 | 2.14 |
| 0.74 | 1.43 | 2.08 | 3.22 |



6,97 x 20,17in