Tubix NA 3000, 930 (BBBL), Wide flood, NL 1 adapter, White



- Product is title 24 compatible
- Delivered standard with Nordic Light 1 circuit adapter. Alternatively available with J or L 1C adapters and NL 3 C adapter
- Four different beam angles for the light distribution
- Highly efficient chip on board LED lightsource
- Available in white, black and grey



Technical specification

Product Code 274-7071-10
Colour White
Control Phase dim
CRI light colour 930 (BBBL)

Delivered lumen output Im 3100

Driver Built in

Light distribution Wide flood

Lightsource LED COB

Mains input voltage 120V

Mains input voltage 120V
Measurements A 6,38
Measurements B 4,77
Measurements C 5,48
Mounting Track
Position 360°/90°
Lifetime L80 B10.

Lifetime L80 B10, 50.000h


Protection For indoor use only

Start Time Instant

System power W 29 Unit inch







| Spot | | Medium | | Flood | | Wide Flood | |
|------|------|--------|------|-------|------|------------|------|
| | 14° | | 26° | | 37° | | 55° |
| m | Ø | m | Ø | m | Ø | m | Ø |
| 1.0 | 0.24 | 1.0 | 0.47 | 1.0 | 0.68 | 1.0 | 1.05 |
| 2.0 | 0.48 | 2.0 | 0.94 | 2.0 | 1.35 | 2.0 | 2.10 |
| 3.0 | 0.72 | 3.0 | 1.41 | 3.0 | 2.03 | 3.0 | 3.15 |