## ZEN MINI 1500, 930, 1C, MEDIUM, 120V, GREY

ITAB

- ✓ Product is title 24 compatible
- Delivered standard with Nordic Light 1 circuit adapter. Alternatively available with J or L 1C adapters and NL 3 C adapter
- ✓ Four different beam angles for the light distribution
- Highly efficient chip onboard LED light source
- Available in white, black and grey

## **TECHNICAL SPECIFICATION**


Product Code
Colour
Control
CRI light colour
Delivered lumen output Im
Driver
EEI
Light distribution
Lightsource
Mains input voltage
Measurements A
Measurements B
Measurements C
Measurements D
Mounting
Position
Lifetime
Protection
Sawing instructions unit
Start Time
System power W
Unit
Weight

325-03041524314 Grev Phase-Dim 930 (BBBL) 1300 Built in Е Medium LED COB 120V 7,65 5,3 3,4 6,45 Track 360°/90° L80 B10, 50.000h IP 20, class I Inch Instant 9,1 inch 1,43









Medium Wide Flood Flood 42° 18 31° 60° Ø m m m 1.0 1.0 0.31 1.0 0.52 0.76 1.16 1.0 0.62 2.0 1.52 2.0 1.05 2.0 232 3.0 1.57 2.28 3.48 0.93 3.0 3.0

ITAB Lighting Europe, Asia, Middle East Phone: +46 910 733 790 info@nordiclight.se ITAB Lighting North America Phone: +1 614 421 8419 na@nordiclight.se Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours