

# Zen Mini 3000, 930, 1C Spot, 120V, Grey




- ✓ Product is title 24 compatible
- ✓ Delivered standard with Nordic Light 1 circuit adapter. Alternatively available with J or L 1C adapters and NL 3 C adapter
- ✓ Four different beam angles for the light distribution
- ✓ Highly efficient chip onboard LED light source
- ✓ Available in white, black and grey



## Technical specification

|                           |                  |
|---------------------------|------------------|
| Product Code              | 325-03071514314  |
| Colour                    | Grey             |
| Control                   | Phase-Dim        |
| CRI light colour          | 930 (BBBL)       |
| Delivered lumen output lm | 2700             |
| Driver                    | Built in         |
| EEL                       | E                |
| Light distribution        | Spot             |
| Lightsource               | LED COB          |
| Mains input voltage       | 120V             |
| Measurements A            | 7,65             |
| Measurements B            | 5,3              |
| Measurements C            | 3,4              |
| Measurements D            | 6,45             |
| Mounting                  | Track            |
| Position                  | 360°/90°         |
| Lifetime                  | L80 B10, 50.000h |
| Protection                | IP 20, class I   |
| Sawing instructions unit  | Inch             |
| Start Time                | Instant          |
| System power W            | 19,4             |
| Unit                      | inch             |
| Weight                    | 1,43             |



| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 18°  | 31°    | 42°   | 60°        |
| m    | m      | m     | m          |
| 1.0  | 1.0    | 1.0   | 1.0        |
| 2.0  | 2.0    | 2.0   | 2.0        |
| 3.0  | 3.0    | 3.0   | 3.0        |
| 0.31 | 0.52   | 0.76  | 1.16       |
| 0.62 | 1.05   | 1.52  | 2.32       |
| 0.93 | 1.57   | 2.28  | 3.48       |