


ZEN MINI, 1500, 930, 3C, SPOT, 120V, WHITE

ITAB

- ✓ Product is title 24 compatible
- ✓ Delivered standard with Nordic Light 1 circuit adapter. Alternatively available with J or L 1C adapters and NL 3 C adapter
- ✓ Four different beam angles for the light distribution
- ✓ Highly efficient chip onboard LED light source
- ✓ Available in white, black and grey

TECHNICAL SPECIFICATION

| | |
|---------------------------|-----------------|
| Product Code | 325-01041514310 |
| Colour | White |
| Control | Phase-Dim |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 1300 |
| Driver | Built in |
| EEL | E |
| Light distribution | Spot |
| Lightsources | LED COB |
| Mains input voltage | 120V |
| Measurements A | 7,65 |
| Measurements B | 5,3 |
| Measurements C | 3,4 |
| Measurements D | 6,45 |
| Mounting | Track |
| Position | 360°/90° |
| Lifetime | L80 B10 50.000h |
| Protection | IP 20, class I |
| Sawing instructions unit | Inch |
| Start Time | Instant |
| System power W | 9,1 |
| Unit | inch |
| Weight | 1,43 |



| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 18° | 31° | 42° | 60° |
| m | m | m | m |
| 1.0 | 1.0 | 1.0 | 1.0 |
| 2.0 | 2.0 | 2.0 | 2.0 |
| 3.0 | 3.0 | 3.0 | 3.0 |
| 0.31 | 0.52 | 0.76 | 1.16 |
| 0.62 | 1.05 | 1.52 | 2.32 |
| 0.93 | 1.57 | 2.28 | 3.48 |