## Zen Mini, 1500, 930, 3C, Wide Flood, 120V, White



- Product is title 24 compatible
- Delivered standard with Nordic Light 1 circuit adapter. Alternatively available with J or L 1C adapters and NL 3 C adapter
- Four different beam angles for the light distribution
- Highly efficient chip onboard LED light source
- Available in white, black and grey



## **Technical specification**

Product Code 325-01041544310

Colour White
Control Phase-Dim
CRI light colour 930 (BBBL)

Delivered lumen output lm 1300
Driver Built in
EEI E

Light distribution Wide flood
Lightsource LED COB
Mains input voltage 120V

Measurements A 7,65
Measurements B 5,3
Measurements C 3,4
Measurements D 6,45
Mounting Track


Position 360°/90°

Lifetime L80 B10 50.000h Protection IP 20, class I

Sawing instructions unit Inch
Start Time Instant
System power W 9,1
Unit inch
Weight 1,43







| Spot |      | Medium |  |      | Flood |  |      | Wide Flood |  |      |
|------|------|--------|--|------|-------|--|------|------------|--|------|
|      | 18°  |        |  | 31°  |       |  | 42°  |            |  | 60°  |
| m    | Ø    | m      |  | Ø    | m     |  | Ø    | m          |  | Ø    |
| 1.0  | 0.31 | 1.0    |  | 0.52 | 1.0   |  | 0.76 | 1.0        |  | 1.16 |
| 2.0  | 0.62 | 2.0    |  | 1.05 | 2.0   |  | 1.52 | 2.0        |  | 232  |
| 3.0  | 0.93 | 3.0    |  | 1.57 | 3.0   |  | 2.28 | 3.0        |  | 3.48 |