## Zen Mini, 3000, 930, 3C, Medium, 120V, Black



- Product is title 24 compatible
- Delivered standard with Nordic Light 1 circuit adapter. Alternatively available with J or L 1C adapters and NL 3 C adapter
- Four different beam angles for the light distribution
- Highly efficient chip onboard LED light source
- Available in white, black and grey



## **Technical specification**

Product Code 325-02071524310

Colour Black
Control Phase-Dim
CRI light colour 930 (BBBL)

Delivered lumen output lm 2700
Driver Built in EEI E

Light distribution Medium
Lightsource LED COB

Mains input voltage 120V
Measurements A 7,65
Measurements B 5,3
Measurements C 3,4
Measurements D 6,45
Mounting Track


Position 360°/90°

Lifetime L80 B10 50.000h Protection IP 20, class I

Sawing instructions unit Inch
Start Time Instant
System power W 19,4
Unit inch
Weight 1,43







Spot		Medium		Flood		Wide Flood	
	18°		31°		42°		60°
m	Ø	m	Ø	m	Ø	m	Ø
1.0	0.31	1.0	0.52	1.0	0.76	1.0	1.16
2.0	0.62	2.0	1.05	2.0	1.52	2.0	2.32
3.0	0.93	3.0	1.57	3.0	2.28	3.0	3.48