## Zen Mini, 3000, 930, 3C, Medium, 120V, Grey



- Product is title 24 compatible
- Delivered standard with Nordic Light 1 circuit adapter. Alternatively available with J or L 1C adapters and NL 3 C adapter
- Four different beam angles for the light distribution
- Highly efficient chip onboard LED light source
- Available in white, black and grey



## **Technical specification**

Product Code 325-03071524310

Colour Grey

Control Phase-Dim
CRI light colour 930 (BBBL)

Delivered lumen output Im 2700
Driver Built in EEI E

Light distribution Medium
Lightsource LED COB

Mains input voltage 120V
Measurements A 7,65
Measurements B 5,3
Measurements C 3,4
Measurements D 6,45
Mounting Track


Position 360°/90°

Lifetime L80 B10 50.000h
Protection IP 20, class I

Sawing instructions unit Inch
Start Time Instant
System power W 19,4
Unit inch
Weight 1,43







| Spot |      | Medium |      | Flood | ł  | Wid    | Wide Flood |      |  |
|------|------|--------|------|-------|----|--------|------------|------|--|
|      | 18°  |        | 31°  |       | 42 | 2°     |            | 60°  |  |
| m    | Ø    | m      | Ø    | m     | Ç  | m      |            | Ø    |  |
| 1.0  | 0.31 | 1.0    | 0.52 | 1.0   | 0. | 76 1.0 |            | 1.16 |  |
| 2.0  | 0.62 | 2.0    | 1.05 | 2.0   | 1. | 52 2.0 |            | 232  |  |
| 3.0  | 0.93 | 3.0    | 1.57 | 3.0   | 2. | 28 3.0 |            | 3.48 |  |