Zen Mini 3000, 930, 1C, Flood, 120V, White



- Product is title 24 compatible
- Delivered standard with Nordic Light 1 circuit adapter. Alternatively available with J or L 1C adapters and NL 3 C adapter
- Four different beam angles for the light distribution
- Highly efficient chip onboard LED light source
- Available in white, black and grey




Technical specification


| Product Code |
|---------------------------|
| Colour |
| Control |
| CRI light colour |
| Delivered lumen output Im |
| Driver |
| EEI |
| Light distribution |
| Lightsource |
| Mains input voltage |
| Measurements A |
| Measurements B |
| Measurements C |
| Measurements D |
| Mounting |
| Position |
| Lifetime |
| Protection |
| Sawing instructions unit |
| Start Time |
| System power W |
| Unit |
| Weight |

325-01071534314 White Phase-Dim 930 (BBBL) 2700 Built in Е Flood LED COB 120V 7,65 5,3 3.4 6,45 Track 360°/90° L80 B10 50.000h IP 20, class I Inch Instant 19,4 inch 1,43









ITAB Lighting Europe, Asia, Middle East Phone: +46 910 733 790 info@nordiclight.se ITAB Lighting North America Phone: +1 614 421 8419 na@nordiclight.se Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours