

FLEXO 3000, 930 (BBBL), FLOOD, BLACK

ITAB

- ✓ Modern, minimalistic and clean-looking ceiling
- ✓ Available in various lumen packages
- ✓ Tool-free installation
- ✓ Available in white, black and grey
- ✓ Tiltable and rotating

TECHNICAL SPECIFICATION

Product Code	306-502-20
Colour	Black
Control	On/off
CRI light colour	930 (BBBL)
Delivered lumen output lm	2841
Driver	Stand alone, included
EEL	E
Light distribution	Flood
Lightsource	LED COB
Mains input voltage	220-240 V
Measurements A	176
Measurements B	65
Measurements C	70
Mounting	Recessed
Position	360°/60°
Lifetime	L80 B10, 50.000h
Protection	IP 20, class III
Sawing instructions diameter	Ø165
Start Time	Instant
System power W	21,6
Unit	mm
Weight	0,9



A= 176mm, B= 65mm, C= 70mm



Spot	Medium	Flood	Wide Flood
14°	27°	38°	56°
m	m	m	m
0	0	0	0
1.0	0.25	0.48	0.69
2.0	0.49	0.95	1.39
3.0	0.74	1.43	2.08
4.0			2.82
5.0			3.56
6.0			4.30
7.0			5.04
8.0			5.78
9.0			6.52
10.0			7.26
11.0			8.00
12.0			8.74
13.0			9.48
14.0			10.22
15.0			10.96
16.0			11.70
17.0			12.44
18.0			13.18
19.0			13.92
20.0			14.66
21.0			15.40
22.0			16.14
23.0			16.88
24.0			17.62
25.0			18.36
26.0			19.10
27.0			19.84
28.0			20.58
29.0			21.32
30.0			22.06
31.0			22.80
32.0			23.54
33.0			24.28
34.0			25.02
35.0			25.76
36.0			26.50
37.0			27.24
38.0			27.98
39.0			28.72
40.0			29.46
41.0			30.20
42.0			30.94
43.0			31.68
44.0			32.42
45.0			33.16
46.0			33.90
47.0			34.64
48.0			35.38
49.0			36.12
50.0			36.86
51.0			37.60
52.0			38.34
53.0			39.08
54.0			39.82
55.0			40.56
56.0			41.30
57.0			42.04
58.0			42.78
59.0			43.52
60.0			44.26
61.0			45.00
62.0			45.74
63.0			46.48
64.0			47.22
65.0			47.96
66.0			48.70
67.0			49.44
68.0			50.18
69.0			50.92
70.0			51.66
71.0			52.40
72.0			53.14
73.0			53.88
74.0			54.62
75.0			55.36
76.0			56.10
77.0			56.84
78.0			57.58
79.0			58.32
80.0			59.06
81.0			59.80
82.0			60.54
83.0			61.28
84.0			62.02
85.0			62.76
86.0			63.50
87.0			64.24
88.0			64.98
89.0			65.72
90.0			66.46
91.0			67.20
92.0			67.94
93.0			68.68
94.0			69.42
95.0			70.16
96.0			70.90
97.0			71.64
98.0			72.38
99.0			73.12
100.0			73.86



165mm