

Amber 5000, 930 (BBBL), Spot w/ glass, Grey


ITAB

- ✓ Discreet and clean-looking ceiling
- ✓ Available in various sizes and lumen packages
- ✓ Available with special oval reflector for sensitive items on display
- ✓ Available in white, black and grey
- ✓ Retractable and rotating



Technical specification

| | |
|------------------------------|-----------------------|
| Product Code | 282-03101110062 |
| Colour | Grey |
| Control | On/off |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 4700 |
| Driver | Stand alone, included |
| EEL | E |
| Light distribution | Spot |
| Lightsource | LED COB |
| Mains input voltage | 220-240 V |
| Measurements A | 170 |
| Measurements B | 115,5 |
| Measurements C | 150 |
| Mounting | Recessed |
| Position | 360°/60° |
| Lifetime | L80 B10, 50.000h |
| Protection | IP 20, class III |
| Sawing instructions diameter | 160 |
| Start Time | Instant |
| System power W | 40,2 |
| Unit | mm |
| Weight | 0,92 |



A= 170mm, B= 115,5mm, C= 150mm

| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 14° | 26° | 37° | 55° |
| m | m | m | m |
| 1.0 | 1.0 | 1.0 | 1.0 |
| 2.0 | 2.0 | 2.0 | 2.0 |
| 3.0 | 3.0 | 3.0 | 3.0 |
| 0.24 | 0.47 | 0.68 | 1.05 |
| 0.48 | 0.94 | 1.35 | 2.10 |
| 0.72 | 1.41 | 2.03 | 3.15 |



160mm