

# Amber 4000, 940, Spot, Grey


ITAB

- ✓ Discreet and clean-looking ceiling
- ✓ Available in various sizes and lumen packages
- ✓ Available with special oval reflector for sensitive items on display
- ✓ Available in white, black and grey
- ✓ Retractable and rotating



## Technical specification

|                              |                       |
|------------------------------|-----------------------|
| Product Code                 | 282-03094010062       |
| Colour                       | Grey                  |
| Control                      | On/off                |
| CRI light colour             | 940                   |
| Delivered lumen output lm    | 4000                  |
| Driver                       | Stand alone, included |
| EEL                          | E                     |
| Light distribution           | Spot                  |
| Lightsource                  | LED COB               |
| Mains input voltage          | 220-240V              |
| Measurements A               | 170                   |
| Measurements B               | 115,5                 |
| Measurements C               | 150                   |
| Mounting                     | Recessed              |
| Position                     | 360°/60°              |
| Lifetime                     | L80 B10, 50.000h      |
| Protection                   | IP 20, class III      |
| Sawing instructions diameter | 160                   |
| Start Time                   | Instant               |
| System power W               | 30,7                  |
| Unit                         | mm                    |
| Weight                       | 0,92                  |



A= 170mm, B= 115,5mm, C= 150mm

| Spot | Medium |     | Flood |     | Wide Flood |     |      |
|------|--------|-----|-------|-----|------------|-----|------|
|      | 14°    | 26° | 37°   |     | 55°        |     |      |
| m    | ø      | m   | ø     | m   | ø          | m   | ø    |
| 1.0  | 0.24   | 1.0 | 0.47  | 1.0 | 0.68       | 1.0 | 1.05 |
| 2.0  | 0.48   | 2.0 | 0.94  | 2.0 | 1.35       | 2.0 | 2.10 |
| 3.0  | 0.72   | 3.0 | 1.41  | 3.0 | 2.03       | 3.0 | 3.15 |



160mm