

Amber Mini 3000, 930 (BBBL), Spot w/ glass, White


ITAB

- ✓ Discreet and clean-looking ceiling
- ✓ Available in various sizes and lumen packages
- ✓ Tool- free installation
- ✓ Available in white, black and grey
- ✓ Retractable and rotating



Technical specification

| | |
|------------------------------|-----------------------|
| Product Code | 296-01071110062 |
| Colour | White |
| Control | On/off |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 2841 |
| Driver | Stand alone, included |
| EEL | E |
| Light distribution | Spot |
| Lightsource | LED COB |
| Mains input voltage | 220-240 V |
| Measurements A | 131 |
| Measurements B | 101 |
| Measurements C | 114 |
| Mounting | Recessed |
| Position | 360°/60° |
| Lifetime | L80 B10, 50.000h |
| Protection | IP 20, class III |
| Sawing instructions diameter | 124 |
| Start Time | Instant |
| System power W | 21,6 |
| Unit | mm |
| Weight | 0,55 |



| Spot | 16° | Medium | 28° | Flood | 40° | Wide Flood | 65° |
|------|------|--------|------|-------|------|------------|------|
| m | ø | m | ø | m | ø | m | ø |
| 1.0 | 0.28 | 1.0 | 0.50 | 1.0 | 0.73 | 1.0 | 1.28 |
| 2.0 | 0.56 | 2.0 | 1.00 | 2.0 | 1.46 | 2.0 | 2.56 |
| 3.0 | 0.83 | 3.0 | 1.51 | 3.0 | 2.18 | 3.0 | 3.84 |



124mm