


# ZYLINDER MICRO 1200, 930 (BBBL), WIDE FLOOD W/ GLASS, BLACK

ITAB

- ✓ Pure and minimalistic/clean design in a small size
- ✓ Four different beam angles for the light distribution
- ✓ Incorporated electronic control gear
- ✓ Highly efficient 'chip on board' LED light source
- ✓ Available in white, black and grey

## TECHNICAL SPECIFICATION

|                           |                  |
|---------------------------|------------------|
| Product Code              | 305-503-20       |
| Colour                    | Black            |
| Control                   | On/off           |
| CRI light colour          | 930 (BBBL)       |
| Delivered lumen output lm | 1150             |
| Driver                    | Built in         |
| EEL                       | E                |
| Light distribution        | Wide flood       |
| Lightsource               | LED COB          |
| Mains input voltage       | 220-240 V        |
| Measurements A            | 166              |
| Measurements B            | 60               |
| Mounting                  | Track            |
| Position                  | 360°/90°         |
| Lifetime                  | L80 B10, 50.000h |
| Protection                | IP 20, class I   |
| Start Time                | Instant          |
| System power W            | 15               |
| Unit                      | mm               |
| Weight                    | 0.4              |



| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 15°  | 27°    | 36°   | 56°        |
| m    | m      | m     | m          |
| 1.0  | 1.0    | 1.0   | 1.0        |
| 2.0  | 2.0    | 2.0   | 2.0        |
| 3.0  | 3.0    | 3.0   | 3.0        |
| 0.26 | 0.47   | 0.65  | 1.06       |
| 0.53 | 0.95   | 1.30  | 2.12       |
| 0.79 | 1.42   | 1.95  | 3.18       |