

Zen Evo Mini, White, 1500, 930, Wide Flood, segmented, Track


ITAB

- ✓ Very minimalistic/clean design
- ✓ Highly efficient chip on board LED light source and segmented reflector for maximum efficacy
- ✓ Integrated, highly efficient electronic control gear in the track adapter
- ✓ Highly efficient chip on board LED light source
- ✓ Available in white, black and grey.



Technical specification

Product Code	367-01041540013
Colour	White
Control	On/off
CRI light colour	930 (BBBL)
Delivered lumen output lm	1520
Driver	Built in
EEL	E
Light distribution	Wide flood
Lightsource	LED COB
Mains input voltage	220-240V
Measurements A	86
Measurements B	106
Measurements C	164
Measurements D	206
Measurements E	134
Mounting	Track
Position	360°/90°
Lifetime	L80 B10 50.000h
Protection	IP 20, class II
Start Time	Instant
System power W	9,8
Unit	mm
Weight	0,49



A= 86 mm, B= 106 mm, C= 164 mm, D= 206 mm

Spot	Medium	Flood	Wide Flood
19°	29°	49°	70°
m	m	m	m
1.0	1.0	1.0	1.0
2.0	2.0	2.0	2.0
3.0	3.0	3.0	3.0
0.31	0.52	0.76	1.16
0.62	1.05	1.52	2.32
0.93	1.57	2.28	3.48