

# Zen Evo Mini, Grey, 2000, 930, Wide Flood, segmented, Track


ITAB

- ✓ Very minimalistic/clean design
- ✓ Highly efficient chip on board LED light source and segmented reflector for maximum efficacy
- ✓ Integrated, highly efficient electronic control gear in the track adapter
- ✓ Highly efficient chip on board LED light source
- ✓ Available in white, black and grey.



## Technical specification

|                           |                  |
|---------------------------|------------------|
| Product Code              | 367-03051540013  |
| Colour                    | Grey             |
| Control                   | On/off           |
| CRI light colour          | 930 (BBBL)       |
| Delivered lumen output lm | 2100             |
| Driver                    | Built in         |
| EEL                       | E                |
| Light distribution        | Wide flood       |
| Lightsource               | LED COB          |
| Mains input voltage       | 220-240V         |
| Measurements A            | 86               |
| Measurements B            | 106              |
| Measurements C            | 164              |
| Measurements D            | 206              |
| Mounting                  | Track            |
| Position                  | 360°/90°         |
| Lifetime                  | L80 B10, 50.000h |
| Protection                | IP 20, class II  |
| Start Time                | Instant          |
| System power W            | 13,3             |
| Unit                      | mm               |
| Weight                    | 0,49             |



A= 86 mm, B= 106 mm, C= 164 mm, D= 206 mm

| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 19°  | 29°    | 49°   | 70°        |
| m    | m      | m     | m          |
| 1.0  | 1.0    | 1.0   | 1.0        |
| 2.0  | 2.0    | 2.0   | 2.0        |
| 3.0  | 3.0    | 3.0   | 3.0        |
| 0.31 | 0.52   | 0.76  | 1.16       |
| 0.62 | 1.05   | 1.52  | 2.32       |
| 0.93 | 1.57   | 2.28  | 3.48       |