

# EasyPoint 1 3000, 930 (BBBL), Medium w/ glass, Black



ITAB

- ✓ Freely deployable in a functional ceiling
- ✓ One family from low to high lumens
- ✓ Easy to move and adjust to changing store layouts
- ✓ Discreet and clean-looking ceiling
- ✓ Available in white, black and grey



## Technical specification

|                           |                    |
|---------------------------|--------------------|
| Product Code              | 321-504-20         |
| Colour                    | Black              |
| Control                   | On/off             |
| CRI light colour          | 930 (BBBL)         |
| Delivered lumen output lm | 2841               |
| Driver                    | Built in           |
| EEL                       | E                  |
| Light distribution        | Medium             |
| Lightsource               | LED COB            |
| Mains input voltage       | 220-240 V          |
| Measurements A            | 41                 |
| Measurements B            | 131                |
| Measurements C            | 103                |
| Measurements D            | 84                 |
| Measurements E            | 73                 |
| Mounting                  | Functional ceiling |
| Position                  | 360°/90°           |
| Lifetime                  | L80 B10, 50.000h   |
| Protection                | IP 20, class I     |
| Start Time                | Instant            |
| System power W            | 21,6               |
| Unit                      | mm                 |
| Weight                    | 1,2                |



| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 16°  | 30°    | 41°   | 54°        |
| m    | m      | m     | m          |
| 1.0  | 1.0    | 1.0   | 1.0        |
| 2.0  | 2.0    | 2.0   | 2.0        |
| 3.0  | 3.0    | 3.0   | 3.0        |
| 0.28 | 0.53   | 0.76  | 1.02       |
| 0.56 | 1.06   | 1.51  | 2.05       |
| 0.83 | 1.59   | 2.27  | 3.07       |