

EasyPoint 1 3000, 930 (BBBL), Flood w/ glass, White



ITAB

- ✓ Freely deployable in a functional ceiling
- ✓ One family from low to high lumens
- ✓ Easy to move and adjust to changing store layouts
- ✓ Discreet and clean-looking ceiling
- ✓ Available in white, black and grey



Technical specification

| | |
|---------------------------|--------------------|
| Product Code | 321-505-10 |
| Colour | White |
| Control | On/off |
| CRI light colour | 930 (BBBL) |
| Delivered lumen output lm | 2841 |
| Driver | Built in |
| EEL | E |
| Light distribution | Flood |
| Lightsource | LED COB |
| Mains input voltage | 220-240 V |
| Measurements A | 41 |
| Measurements B | 131 |
| Measurements C | 103 |
| Measurements D | 84 |
| Measurements E | 73 |
| Mounting | Functional ceiling |
| Position | 360°/90° |
| Lifetime | L80 B10, 50.000h |
| Protection | IP 20, class I |
| Start Time | Instant |
| System power W | 21,6 |
| Unit | mm |
| Weight | 1,2 |



| Spot | Medium | Flood | Wide Flood |
|------|--------|-------|------------|
| 16° | 30° | 41° | 54° |
| m | m | m | m |
| 1.0 | 1.0 | 1.0 | 1.0 |
| 2.0 | 2.0 | 2.0 | 2.0 |
| 3.0 | 3.0 | 3.0 | 3.0 |
| 0.28 | 0.53 | 0.76 | 1.02 |
| 0.56 | 1.06 | 1.51 | 2.05 |
| 0.83 | 1.59 | 2.27 | 3.07 |