


MOVEFLOW MODULAR

ITAB

- ✓ Un design clair et compact avec des modèles alternatifs pour un large éventail d'applications (X1 / X2 / Hybrid) et un aspect personnalisable avec vernis possible dans toutes les teintes RAL.
- ✓ Plusieurs modules de paiement en espèces disponibles en plus du paiement par carte. Des configurations facultatives de rangements et de rayonnage pour certains modèles
- ✓ Une protection contre les erreurs et les tentatives de fraudes grâce à une balance de vérification des achats.
- ✓ Modèle hybride : une solution compacte et intelligente permettant de passer de l'encaissement conventionnel au libre-service, et facile à adapter aux brusques changements d'affluence
- ✓ Modèle hybride : améliore la satisfaction des clients et permet une affectation optimale du personnel.



TECHNICAL SPECIFICATION

Dimensions HxLxW mm	Width: 1410 - 1750 mm Depth: 720 mm Height: 1400 mm
Weight kg	170 - 200kg
Certifications	CE
Voltage	220-240VAC 50-60Hz Max 3A in total
Operating temperature	+10 °C to +30 °C
Customer display	Yes
Options	Yes
Packing area alternatives	Wing Sizes: X1 / X2
Payment options	Card & Glory / OEM prepared
Ergonomic norms	ADA guidelines
Customisable	Yes
Installation	Indoor
Scanners	3550, 9300 and 9800
Security solution	Weight verification by security scale
Operating conditions	Ambient humidity: 30-80% Storage humidity: 30-80%