

MOVEFLOW CLASSIC

ITAB

- ✓ Et minimalt, strippet design med alternative modeller for en rekke bruksområder (X1, X2, Mini).
- ✓ Beskytter mot feil og svindelforsøk med kontrollvekt.
- ✓ Integreerte kortbetalingsløsninger for minimal størrelse, men full funksjonalitet.
- ✓ Utseende kan tilpasses med valgfri lakk i ønsket RAL-farge eller fargesammensetning.
- ✓ Avhengig av modell kan MoveFlow Klassisk utstyres med forskjellige hyllekonfigurasjoner.



TECHNICAL SPECIFICATION

Dimensions HxLxW mm	Width: 795 - 1775 mm Depth: 625 mm Height: 1365 mm
Weight kg	80 - 140kg
Certifications	CE/UL
Voltage	220-240VAC 50-60Hz Max 3A in total
Operating temperature	+10 °C to +30 °C
Customer display	Yes
Options	Yes
Packing area alternatives	Wing Sizes: Mini / X1 / X2
Payment options	Card Payment
Ergonomic norms	ADA guidelines
Customisable	Yes
Installation	Indoor
Scanners	3550, 9300 and 9800
Security solution	Weight verification by security scale
Operating conditions	Ambient humidity: 30-80% Storage humidity: 30-80%