

MoveFlow Classic

ITAB

- ✓ En minimal, avskalad design med alternativa modeller för en mängd olika situationer (X1, X2, Mini).
- ✓ Utrustad med bedrägeriskydd via våg för köpvalidering.
- ✓ Komplet funktionaltitet med integrerade kortbetalningslösningar för minimal storlek.
- ✓ Anpassningsbart utseende med lack i valfri RAL-färg eller profilmärger.
- ✓ Beroende på modell kan MoveFlow Classic utrustas med olika hyllkonfigurationer.



Technical specification

Dimensions HxLxW mm

Width: 795 - 1775 mm Depth:
625 mm Height: 1365 mm

Weight kg

80 - 140kg

Certifications

CE/UL

Voltage

220-240VAC 50-60Hz Max 3A in
total

Operating temperature

+10 °C to +30 °C

Customer display

Yes

Options

Yes

Packing area alternatives

Wing Sizes: Mini / X1 / X2

Payment options

Card Payment

Ergonomic norms

ADA guidelines

Customisable

Yes

Installation

Indoor

Scanners

3550, 9300 and 9800

Security solution

Weight verification by security
scale

Operating conditions

Ambient humidity: 30-80%
Storage humidity: 30-80%



ITAB HQ Sweden

Phone: +46 36 31 73 00
info@itab.com

Local contact

Please visit
www.itab.com/contact

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours