

- ✓ Totalmente ignífugo y seguro con función de ruptura patentada.
- ✓ Monitorización y configuración totalmente remota a través de la plataforma OnRed.
- ✓ Huella mínima gracias al diseño delgado y las puertas correderas.
- ✓ Fácil instalación con comunicación de puerta inalámbrica.
- ✓ Parte de una familia de puertas versátil, disponible en tres tamaños.



Technical specification

| | |
|-----------------------|---|
| Dimensions HxLxW mm | 900 (pair): 1125x2202x140 900 High (pair): 1812x2202x140 1200 (pair): 1125x2802x140 |
| Weight kg | 900/900 high/1200 (pair): 140/178/158 kg |
| Certifications | CE |
| Voltage | 24 VAC, 110-240 VAC |
| Operating temperature | 0-35 |
| Automatic Panic Reset | Yes |
| Gate Arm options | Yes |
| LED light | Yes, Customisable color for gate body and gate arm |
| Synchronized opening | Yes, wireless |
| Panic Alarm | Yes |
| Communication | Cloud connectivity through OnRed |
| Options | Remote control, Connection to fire alarm. Overhead sensor, Service desk switch, RFID reader |
| Customisable | Yes, Color of gate body, LED-color, Gate arm Logo |
| Installation | Indoor |
| Scanners | Optional |
| Security solution | Radar options, Gate arm options |
| Sustainability | 49,5% lower Carbon footprint than SigmaGate 1 |
| Operating conditions | Indoor |

