

- ✓ Beheer en configureer uw poorten naadloos via het OnRed-platform, vanaf elke locatie.
- ✓ Geniet van een eenvoudige installatie met draadloze poortcommunicatie, zonder lastige bekabeling.
- ✓ Plan de ECO-stand, permanente open-instellingen en openingstijden voor optimale efficiëntie.
- ✓ Aangepaste alarminstellingen met realtime waarschuwingen en meldingen via OnRed.
- ✓ Stem de LED-kleuren en poortkleuren af op de branding van uw winkel.



## Technical specification

Dimensions HxLxW mm	1125*120*120 (foot plate 182)
Weight kg	16
Certifications	CE
Voltage	24 VAC, 110-240 VAC
Operating temperature	0-35° C
Automatic Panic Reset	Yes
Gate Arm options	Yes
LED light	Yes, Customisable colour for gate body and gate arm
Opening angle	180°
Synchronized opening	Yes
Panic Alarm	Yes, with possibility to real time notification via OnRed
Communication	Cloud connectivity through OnRed, Remote control, Connection to fire alarm
Options	Overhead sensor, Service desk switch, RFID reader
Customisable	Yes, Colour of gate body, LED-colour, Gate arm Logo
Installation	Indoor
Scanners	Optional. ScanMaster or ScanMaster XD
Security solution	Radar options, Gate arm options and possibility to real time notification via OnRed
Operating conditions	Indoor

