

- ✔ Gestione y configure sus portillones de manera eficiente desde cualquier lugar a través de la plataforma OnRed.
- ✔ Disfrute de una instalación sencilla con comunicación inalámbrica de puerta, lo cual elimina la necesidad de cables engorrosos.
- ✔ Programe el modo ECO y ajustes de apertura permanente, y almacene las horas de funcionamiento para optimizar la eficiencia.
- ✔ Ajustes de alarma personalizados con alertas y notificaciones en tiempo real a través de OnRed.
- ✔ Personalice los colores de los LED y los portillones para que coincidan con la marca de su tienda.



## Technical specification

Dimensions HxLxW mm	1125*120*120 (foot plate 182)
Weight kg	16
Certifications	CE
Voltage	24 VAC, 110-240 VAC
Operating temperature	0-35° C
Automatic Panic Reset	Yes
Gate Arm options	Yes
LED light	Yes, Customisable colour for gate body and gate arm
Opening angle	180°
Synchronized opening	Yes
Panic Alarm	Yes, with possibility to real time notification via OnRed
Communication	Cloud connectivity through OnRed, Remote control, Connection to fire alarm
Options	Overhead sensor, Service desk switch, RFID reader
Customisable	Yes, Colour of gate body, LED-colour, Gate arm Logo
Installation	Indoor
Scanners	Optional. ScanMaster or ScanMaster XD
Security solution	Radar options, Gate arm options and possibility to real time notification via OnRed
Operating conditions	Indoor





**ITAB HQ Sweden**  
Phone: +46 36 31 73 00  
info@itab.com

**Local contact**  
Please visit  
[www.itab.com/contact](http://www.itab.com/contact)

*Please note that this product sheet  
is for a specific product and colour.  
The pictures may show examples  
of other available colours*