MoveFlow Classic



A minimal, stripped design with alternative models for a wide variety of applications (X1, X2, Mini).

- Protected against mistakes and fraud attempts with weighing scale for purchase validation.
- Integrated card payment solutions for minimal size but complete functionality.
- Adaptable appearance with optional lacquer in any RAL colour or set of colours.
- Depending on model, MoveFlow Classic can be equipped with different shelving configurations.



Technical specification

- Dimensions HxLxW mm
- Weight kg Certifications Voltage
- Operating temperature Customer display Options Packing area alternatives Payment options Ergonomic norms Customisable Installation
- Security solution

Scanners

Operating conditions

Width: 795 - 1775 mm Depth: 625 mm Height: 1365 mm 80 - 140kg CE/UL 220-240VAC 50-60Hz Max 3A in total +10 °C to +30 °C Yes Yes Wing Sizes: Mini / X1 / X2 Card Payment **ADA** guidelines Yes Indoor 3550, 9300 and 9800 Weight verification by security scale Ambient humidity: 30-80% Storage humidity: 30-80%





ITAB HQ Sweden Phone: +46 36 31 73 00 info@itab.com **Local contact** Please visit www.itab.com/contact Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours